TECHNICAL SPECIFICATIONS

2025 KTM SX-E 3

ENGINE

Electric motor	**48 V - BLDC MOTOR WITH OUTER ROTOR**
Torque	**10.5 NM**
Max. motor speed	**5500 RPM**
Charging time 100 %	**160 MIN.**
Rated output	**2 KW / 3,200 RPM**
Traction battery	**LITHIUM-ION**
Charger line voltage	**85-270**
Charging power	**350 W**
Charging time 80 %	**120 MIN.**

CHASSIS

Frame design	**CHROME-MOLYBDENUM STEEL CENTRAL-TUBE FRAME**
Rear subframe design	**GLASS FIBER REINFORCED PLASTIC**
Handlebar	**TAPERED ALUMINUM Ø 28/22/18 MM**
Front brake	**DISC BRAKE**
Rear brake	**DISC BRAKE**
Front brake disc diameter	**160 MM**
Rear brake disc diameter	**160 MM**
Wheels	**1.60 X 10"; 1.60 X 10"**
Tyre width (front)	**60**
Tyre height (front)	**100**
Tyre width (rear)	**2.75**
Tyre height (rear)	**10**
Chain	**415, NON-SEALED**
Steering head angle	**66 °**

SUSPENSION

Front suspension	**XACT 35 WP UPSIDE-DOWN FORK, Ø 35 MM**
Rear suspension	**WP MONOSHOCK**
Suspension travel (front)	**144 MM**
Suspension travel (rear)	**129 MM**
Steering head angle	**66 °**
Fork offset	**22 MM**

DIMENSIONS

Seat height	**682 MM**
Wheelbase	**1025 ± 10 MM**
Ground clearance	**187 MM**